



MINIMUM DIMENSIONS				
A	B	C	D	E
2"	6"	4"	2"	3"

### SIGN PROFILE

#### NOTES:

1. ON ALL STREETS WITH DESIGNATED OR POSTED SPEEDS OF 25 MPH OR LESS, INITIAL UPPER-CASE LETTERS SHALL BE 4 INCHES IN HEIGHT AND LOWER-CASE LETTERS 3 INCHES IN HEIGHT.
2. LETTER STYLES FOR STREET NAME AND SUFFIX SHALL BE 4-INCH SERIES 'B' FROM THE *STANDARD ALPHABETS FOR HIGHWAY SIGNS MANUAL*.
3. BLANKS FOR 6-INCH EXTRUDED SHALL BE A MINIMUM 0.125 INCH GAUGE WITH 6063 T5 OR 6063 T6 ALODINE COATED ALUMINUM SUBSTRATE.
4. THE MINIMUM LENGTH SHALL BE 24 INCHES.
5. BOTH SIDES OF STREET NAME SIGNS SHALL BE GREEN (PUBLIC) OR BLUE (PRIVATE) *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
6. ALL LETTERS AND NUMBERS SHALL BE WHITE *3M HIGH INTENSITY PRISMATIC (HIP)* REFLECTIVE SHEETING.
7. MOUNTING HARDWARE: SEE DRAWING 523.



Public Works Standard Drawings

STREET NAME SIGN WITH 4-INCH LETTERING  
FOR 25 MPH OR LESS SPEED LIMITS

SCALE	NTS
DATE	JUL '25
REV.	1
ENGR.	DW
DRAWN	KAE
DRAWING NO.	521